

12/2018

# **Mod: AD1N/HG-R2**

**Production code: AE07V2500-DM**



**Diamond**  
catering equipment

<b>Modello</b> - Model - Model - Gerätetyp		<b>AD1N/HG-R2</b>
Code Production		AE07V2500-DM
<b>Descrizione</b> - Description - Description - Beschreibung		<b>700 PV TN</b>
<b>Tipo di teglie</b> - Trays type - Type de plateaux - Blechetyp - Tipo de fuentes		GN 2/1
<b>Range</b>		0°C +10°C
<b>Scheda Elettronica</b> - Electronic card		EVCO EVX214
<b>Funzionamento</b> - Operating Mode - Mode de fonctionnemen - Betriebsmodus <b>S</b> = Statico - Static - Statique - Stille Kühlung - <b>V</b> = Ventilato - Ventilated - Ventilte - Umluftkühlung		<b>V</b>
<b>Capacità lorda</b> - Gross Capacity - Capacité brute - Bruttovolumen		700
<b>Dimensioni esterne</b> - External Dimension - Dimensions externes - ußenabmessungen		
Lunghezza - Width -Largeur - Breite		mm 770
Profondità / con porte aperte - Depth / with open doors		mm 820/1520
Profondeur avec portes ouverte - Tiefe/mit geöffneter Tür		
Altezza - Height - Hauteur - Höhe		mm 2025
<b>Dimensioni interne</b> - Internal Dimension - Dimensions internes - Innenabmessungen		
Lunghezza - Width -Largeur - Breite		mm 600
Profondità - Depth - Profondeur - Tiefe		mm 670
Altezza - Height - Hauteur - Höhe		mm 1440
<b>Porte</b> - Doors - Portes - Türen		1, Glass
<b>Dotazione Standard</b> - Standard Equipment - Equipement standard - Standardausstattung		Griglia plastificata - Plastic-Coated Grid Grille Plastifiée - Kunststoff-Beschichtetes Gitter 530x650 3
<b>Luce interna</b> - Internal light - Eclairage intérieure - Innerbeleuchtung		② Full Glass Vertical Light
<b>Serratura</b> - Lock - Serure - Schloss		② ●
<b>Sbrinamento</b> - Defrost - Dégivrages - Abtauen		
Type		Hot Gas
N° Defrost in 24 hrs.		Automatic
Evaporazione acqua sbrinamento - Evaporation of defrost water Evaporation eau de dégivrage - Tauwasserverdunstung		Automatic by Hot Gas
<b>Compressor</b>		<b>embraco</b>
Model		EMT6165U
Potenza - Power - Puissance - Leistung		HP 1/3
T° Evaporation		°C -10
Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung		watt 520
<b>Refrigerante</b> - Refrigerant type - Réfrigérant type - Kältemitteltyp		GWP R290 / 3
<b>Quantità di refrigerante</b> - Refrigerant quantity - Quantité de réfrigérant - Kältemittelmenge		gr 90
<b>Potenza assorbita</b> - Total Power - Puissance - Leistung		watt 330W 2,1A / 350W 2,3A
<b>Tensione alimentazione</b> - Supply Voltage - Tension d'alimentation - Anschlussspannung		V 230V~ 50Hz
<b>220V/60Hz Voltage</b>		<input type="checkbox"/>
<b>Peso Netto</b> - Net weight - Poids net - Netto Gewicht		kg 150
<b>Volume</b> - Volume - Volume - Volumen		mc 1,5
<b>Versione Predisposta</b> - Remote version - Version sans groupe - Modelle ohne Aggregat Sbrinamento elettrico - Electrical defrosting - Dégivrage électrique - Elektrische Abtaung		---
<b>Efficienza Energetica</b> - Energy Efficiency - Classe Énergie - Energieeffizienzklasse		D
<b>Energia</b> - Energy - Énergie - Energie		kWh / annum 831
<b>Volume Netto</b> - Net Volume - Volume Net - Nettoinhalt		l 472
<b>Classe Climatica</b> - Climate Class - Classe Climatique - Klima Klasse		4 30°C-55%

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung  =Optional

