

01/2019

Mod: **SLID-14-R2**

Production code: 06.02.0.BR.50.2.F.230.50 (430 CHV/VCI)



Diamond
catering equipment



MODELO MODEL MODÈLE MODELO	550CHV/VCI	430CHV/VCI	320CHV/VCI
Alimentação Mains supply Raccordement Alimentación	220V~240V/50Hz	220V~240V/50Hz	220V~240V/50Hz
Potência nominal Nominal power Puissance nominale Potencia nominal [W]	260	226	224
Consumo de energia Energy consumption Conso. d'énergie Consu. de energia	2,5 kWh/24h	2,2 kWh/24h	1,9 kWh/24h
Condensador ventilado Fan assisted condenser Condens. ventilé Condens. ventilado	●	●	●
Sinalização Indicator lights Voyants de contrôle Luces piloto:			
- Rede Mains Alimentation Corriente	●	●	●
- Congelamento rápida Fast freeze Congélation rapide Congelación rápida	●	●	●
- Alarme Alarm Alarme Alarma	●	●	●
Volume bruto Gross volume Volume brut Volumen bruto [lts]	527	391	289
Volume útil Net volume Volume net Volumen neto [lts]	426	315	231
Cestos Baskets Paniers Cestos (standard / opcional máximo)	8	6	5
Cestos Baskets Paniers Cestos (standard / opcional máximo)	6 / 6	5	4
Termómetro Analógico Analogue thermometer Thermomètre A T. analógico	1	1	1
Termómetro Digital Digital Thermometer Thermomètre numérique T. digital	■	■	■
Dobradiças c/ mola Counter-balanced Charnières compensées Bisagras c/ muelle	○	○	○
Dimensões Dimensions Dimensions Dimensiones [cm]	181 x 60 x 83	140 x 60 x 83	110 x 60 x 83
Dim. embalagem Packed dimensions Dim. emballage Dim. embalaje [Cm]	183 x 70 x 94	143 x 70 x 92	112 x 70 x 92
Peso (bruto/líquido) Weight (gross/net) Poids (brut/net) Peso (bruto/neto) [kg]	99 / 64	66 / 58	60 / 52

Your professional partner