

07/2014

Mod: RS15/AT

Production code: B8020143 (C150A) 



Diamond
catering equipment

5.2.1 Specifications table

	COLIBRI' 150 A	
TECHNICAL CHARACTERISTICS		
Width x depth x height	(mm)	200 x 560 x 590
Weight	(kg)	17
Sound level	(db (A))	< 70
membrane	(n°)	1
Activated carbon filter		
SUPPLY WATER CHARACTERISTICS		
Type of water		Drinkable
Minimum water temperature	(°C)	5
Maximum water temperature	(°C)	45
Minimum supply flow rate	lit/hr	700
Maximum supply pressure	(bar)	3.5
Minimum supply pressure	(bar)	1
OPERATING ENVIRONMENT		
Maximum relative humidity	(%)	90
Minimum air temperature	(°C)	3
Maximum air temperature	(°C)	40
ELECTRICAL CHARACTERISTICS		
Supply type		Single-phase + earth
Voltage rating	(V)	230
Frequency	(Hz)	50
Power	(W)	186
Circuit board protection fuse type		
PERMEATE CHARACTERISTICS		
Maximum flow at 15°C	lit/hr	approx. 150
Permate/concentrate production ratio		approx. 1:1.5
REPLACEMENT CONDITIONS		
Activated carbon filter	(l)	12,000
Reverse osmosis membrane		When blocked