



**MOD : WR-PV60-XP**

**Production code : QRX600**

**03/2025**

# ABS | Upright Cabinets

REFRIGERATED UPRIGHT ► GN2/1 ► INOX



## GENERAL FEATURES

|   |   |
|---|---|
| GN2/1 Refrigerated upright (600 Lt.)  | • |
| Gray coated plate external cabinet and door in stainless steel, thermoformed internally | • |
| Roll-bond evaporator system with fan assisted cooling                                   | • |
| Automatic compressor cycle defrost  | • |
| Foaming Agent Cyclopentane (60mm per side)  | • |
| Digital Thermostat  | • |
| Removable Gasket  | • |
| Reversible door   | • |
| Handle along door profile   | • |
| Doors lock fitted as standard   | • |
| Adjustable shelves: 4 Pcs + 1 BOTTOM Shelf  | • |
| N.2 Adjustable feet + N.2 Rollers at the back   | • |
| Energy efficiency class: D  | • |

## TECHNICAL SPECIFICATIONS

|                                  |                     |
|----------------------------------|---------------------|
| Capacity                         | <b>600 L</b>        |
| Temperature                      | <b>+2°C ~ +10°C</b> |
| Consumption                      | <b>1.94 kWh/24h</b> |
| Rated Power                      | <b>200 W</b>        |
| Noise level                      | <b>57 dB(A)</b>     |
| Net Weight                       | <b>85 Kg</b>        |
| Gross Weight                     | <b>97 Kg</b>        |
| External Dimensions (WxDxH mm)   | <b>780x730x1890</b> |
| Internal Dimensions (WxDxH mm)   | <b>660x585x1680</b> |
| Packaging dimensions (WxDxH mm)  | <b>812x757x2030</b> |
| Loading quantities 20'/40'/40'HQ | <b>21/42/42</b>     |

## CERTIFICATION

CE RoHS

# WR-PV60-XP



## DETAILS



Cabinet suitable for GN2/1 pans

Cabinet suitable for N.2 GN1/1 pans

Digital Thermostat

Lock fitted as standard

## PRODUCT DIMENSIONS

